

Bench Oven Specifications

MODEL NO.	INSIDE DIMENSION	CUBIC FT. CAPACITY	OUTSIDE DIMENSION	WATTAGE	AMPS	SHIPPING WEIGHT	MAX TEMP
21-250	25.5WX20HX24D	7	33WX24HX35.5D	1110	9.65	180#	149°C/300°F
21-350	25.5WX20HX24D	7	33WX24HX35.5D	2110	18.34	180#	225°C/437°F
51-550	25.5WX20HX22.5D	6.60	33WX24HX35.5D	2800	12.17	185#	287°C/550°F
31-350	25.5WX30HX24D	10.6	33WX34HX35.5D	2110	18.34	212#	225°C/437°F
21-350E	25.5WX20HX24D	7	33WX24HX35.5D	2110	18.34	180#	450°F
31-350E	25.5WX30HX24D	10.6	33WX34HX35.5D	2110	18.34	212#	450°F

NOTES:

- ◆ Outside dimensions with exhaust chamber on models 21 & 51 is 33WX24HX35.5D; on model 31 is 33WX34HX35.5D.
- ◆ Outside depth dimensions are measured from the electrical cover in the back to the outside of the door. The width includes the control panel on the side.
- ◆ All bench ovens have aluminized interiors. High impact thermoplastic **cool** handles are used.
- ◆ Model 51-550 has a 6' electrical cord with a 3 prong grounded plug. No direct wiring is necessary.
- ◆ Models 21-350 and 31-350 have a 6' electrical cord with a 3 prong **20AMP** plug.
- ◆ The amps rating above is based on 115 volt for all ovens except the model 51-550 which is 230 volt.
- ◆ E Models have digital controllers. All other are dial controllers.