



Carbon Monoxide Meter

CO 1000



*Measure CO quick and easy in
working and living environments.*

Features/Benefits

- Backlit LCD
- Automatic calibration
- Max Hold and Data Hold
- Auto Power Off
- Audible Alarm
 - From 35 PPM to 200 PPM, the beeper sounds periodically
 - Above 200 PPM, the beeper sounds continuously
- Carrying case included

SEALED UNIT PARTS CO., INC.
PO Box 21, 2230 Landmark Place, Allenwood, NJ USA
732-223-6644 • Fax 732-223-1617
www.supco.com • info@supco.com



Applications

- Check dangerous CO levels
- Identify malfunctioning equipment

Specifications

Measurement range	0 to 1000 PPM
Measurement Resolution	1 PPM
Accuracy	5% or ± 10 PPM (0-100 PPM) 10% ± 10 PPM (>100PPM)
Warm Up Period	< 2 Seconds
Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-22°F to 140°F (-30° to 60°C)
Operating Humidity	0-99% Relative Humidity (non-condensing)
Auto Power Off	After 15 minutes of inactivity
Sensor Type	Stabilized electrochemical Gas-specific (CO)
Typical Sensor Life	3 years
Warranty	1 year
Battery	9V (included)

SEALED UNIT PARTS CO., INC.

PO Box 21, 2230 Landmark Place, Allenwood, NJ USA
732-223-6644 • Fax 732-223-1617
www.supco.com • info@supco.com

F311-0403